

SABER® M700™

APO
ASHBURY PRECISION ORDNANCE®
The Precision Long Range Rifle Specialists



SABER M700-308TRX

LONG RANGE

TACTICAL RIFLE SYSTEM

Modular by Definition... Performance Engineered by Design

SABER® M700™-308TRX

SABER-M700.com

TACTICAL RIFLE SYSTEM

Ashbury Precision Ordnance’s SABER M700 Tactical Rifle X (TRX) is the operational standard for intermediate to long range tactical rifle platforms. The SABER M700 Tactical Rifle is designed to provide demanding users with an accurate and ergonomically adjustable tactical rifle designed for reliable service during tough field conditions. Chambered for the versatile .308 Winchester cartridge (7.62mm), the SABER M700 Tactical Rifle X provides long range shooters with enhanced ± ½ MOA precision out to distances of 1,000 yards.

Designed for accuracy and dependability, the SABER M700 Tactical Rifle provides shooters with many quality features. **The Action:** Remington’s proven Model 700 bolt action receiver manufactured from quality carbon steel, precision trued and blueprinted “X” by experienced APO Precision Weapon Section gunsmiths & coated with a tough, corrosion-resistant Cerakote ceramic finish. **The Barrel:** 20 inch match grade stainless steel - medium Palma contour– threaded muzzle, and highly efficient muzzle brake suppressor adapter. **The Trigger:** Reliable, adjustable single-stage trigger that breaks cleanly and crisply at 3 lbs.

The Patented Rifle Chassis: The SABER M700 Tactical Rifle is built on Ashbury’s ergonomically adjustable MRCS-AR MOD-1 modular rifle chassis system. SABER rifle chassis are rugged, reconfigurable, require no bedding to obtain optimal accuracy and are impervious to extreme wet, hot and cold weather conditions. **The Ergonomic Shoulder Stock:** The SABER M700 Tactical Rifle features the PBA-H (Push Button Adjustable Hybrid) with length of pull, vertical recoil pad drop and thumbscrew cheek piece height adjustments. Stock adjustments are completely tool-less and positive locking! The PBA-H shoulder stock is fitted with a butt hook as standard equipment for non-shooting hand support and a rapidly adjustable 3-position field monopod is available as a user-installable option.

SABER modular rifle chassis feature a user-adjustable hand grip, to change distance-to-trigger (for large and small hands) with a comfortable 11° grip angle. Optional hand grips and grip angles are available. The SABER M700 Tactical Rifle is fitted with an ambidextrous paddle lever magazine catch-release and comes with one 10 round AICS patterned magazine.

The SABER M700 Tactical Rifle’s AR-08 aluminum alloy MOD-1 forend has a unique octagonal design with M-LOK® accessory rail mounting locations at 3, 6, 9 and 12 o’clock positions. The SABER M700 Tactical Rifle additionally features Ashbury’s patented, continuous one-piece MIL-STD 1913 20 MOA unitized monolithic top rail that provides structural rigidity for long range accuracy, secure in-line mounting of the rifle scope, and clip-on night vision or thermal imager device. Shoot-ability, comfort, ergonomic adjustability, modularity, and low-felt recoil with ± ½ MOA accuracy are hallmarks of the SABER M700 TRX Tactical Rifle.



Shown with Optional Accessories

Utility & Design Patents at
APO-Patents.com



Trusted to Make it Better!

CALIBER

.308 Winchester (optional 6.5 Creedmoor)

ACTION

APO Accurized Remington Model 700® AAC-SD™ Short Action Receiver, Carbon Steel, Cerakote Armor Black Finish

BOLT

Two-Lug Bolt Design with Tactical Bolt Knob

TRIGGER

Single-Stage Adjustable Enclosed Body (set to 3 lbs.; optional 2-stage)

BARREL

- APO Accurized.308 - 20” Hammer Forged Carbon Steel, 1:10 Twist, Muzzle Threaded ¾-24
- APO Accurized 6.5CM - 22” Hammer Forged Carbon Steel, 1:8 Twist, Muzzle Threaded ¾-24

MUZZLE BRAKE

AAC Blackout 51T (alternate manufacturer and models available)

SOUND SUPPRESSOR (optional)

AAC 762SD (alternate manufacturer and models available)

RIFLE CHASSIS - MODULAR

SABER RSA-A3 MRCS-AR MOD-1

SHOULDER STOCK - ERGONOMIC/ADJUSTABLE

PBA-H - Push Button Adjustable Hybrid, Tool-less Positive Locking

- Limbsaver Premium Recoil Pad
- Butt Hook, Interchangeable
- Flush Cup Sling Swivel Sockets x2
- Monopod, 3-Position (optional)

STOCK INTERFACE

Double Locking Alloy Folding Hinge, Tension Adjustable (optional Fixed & Locking Stainless Steel)

MAGAZINE - BOX

10rd Detachable AICS Patterned (x1) (optional 5/10rd Polymer Mags)

HAND GRIP

Ergo Grip Slimline (Changeable AR-15/M-16 Style)

GRIP ANGLE ADAPTERS

11° (optional 17.5° and 27°)

FOREND

- AR-08 Octagonal Aluminum Alloy M-LOK® Accessory Mounting Locations at 3-6-9-12 o’clock Positions
- M-LOK Flushcup Socket (x1)

MONOLITHIC PICATINNY SCOPE RAIL

20 MOA Slant, MIL-STD 1913, Co-Linear Mounted Day & Night Optics

ACCESSORY RAILS

- M-LOK Picatinny Accessory Rails (optional)
- M-LOK Accessories Kit (optional)

SURFACE COATINGS

Hard Coat Anodized and Cerakote Coating

COLOR

- SABER Chassis: Black MIL -A-8625 Type III Hard Coat Anodized
- Barreled Action: Armor Black

ACCURACY

±½ MOA with Match-Grade Ammunition

PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (optional)
- Nylon padded Field Carry Bag (optional)

BASE RIFLE WEIGHT & DIMENSIONS

.308Win - 11.3 lbs. / Extended Length 41” / Folded Length 31.5” (approx)

.6.5CM - 11.5 lbs. / Extended Length 43” / Folded Length 33.5” (approx)

Specifications are Subject to Change. Custom Configurations Available.

SABER® M700™-308TRX BALLISTICS & ACCESSORIES

SABER-M700.com

TACTICAL RIFLE SYSTEM

EXTERNAL BALLISTICS

.308 Winchester 175gr Match 2600fps .547BC

Distance		Elevation	Elevation	Velocity
Yards	Meters	MOA	MILS	FPS
100	91	0	0	2434
200	183	1.25	0.4	2274
300	271	3.75	1.1	2120
400	366	7.00	2.0	1970
500	457	10.50	3.1	1826
600	549	14.50	4.2	1688
700	640	19.25	5.6	1555
800	732	24.25	7.1	1428
900	823	30.00	8.8	1307
1000	914	36.75	10.7	1197
1100	1006	44.25	12.8	1107

Station Pressure: 29.53 in. Hg.	Caliber: .308 Winchester	Bullet Weight: 175gr
Humidity: 78%	Bullet Type: BTHP Open Tip Match	Ballistic Coefficient: 0.547 (G1)
Temperature: 59°	Velocity: 2600± Feet Per Second	Rifle: SABER M700-308TRX 20" BBL
Elevation: 0ft ASL		

Standard Metro Atmospheric Conditions

ACCESSORIES

- Premium Rifle Scopes
- SABER EO Scope Rings
- Monopod, 3-Position Adjustable
- Bipod
- Sling - Shooting / Carry
- Sound Suppressor
- Precision Rifle Cleaning Kit
- Protective Padded Nylon Field Bag
- Hard Transit Case - Custom Foam Interior
- Ballistic Software & Hand-held Computer
- Ballistic Calculator .308Win - Analog (no batteries required)
- Magazines, Box 5 & 10rd Capacity
- SABER Field Multi-Tool
- Anti-Cant Device, Scope Mounted
- Angle Cosine Indicator (ACI)
- Spare Fasteners Package
- Armorer Repair Parts Kit
- Sniper's Field Tool Kit
- Observation Spotting Scope / TACT 3 Compact Tripod Kit
- RSTA-II Tripod Shooting System

Contact us for Complete Rifle Packages, Match-grade Ammunition, Armorer & Precision Rifle Marksmanship Training

COATINGS & FINISHES



Other Colors & Coatings Available



Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600
AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com